## **BLAZER PRODUCTS**

## Safety Data Sheet

Section 1	PRODUCT INDENTIFICATION
Product Name	Liquefied Petroleum Gas, Butane
Recommended Use	As an ignition fuel for butane torches and lighters
Synonyms/Trade Names	Butane, Blazer Butane
Restrictions on Use	None known
Manufacturer	Blazer Products, 88 Allen Blvd Farmingdale, NY USA 11735
Emergency Phone Number	Chemtrec 800-424-9300

Section 2	HAZARD INDENTIFICATION		
DANGER	Highly flammable liquid and vapor		
GHS Classification	Flammable Gas Category 1		
	Gas under pressure, Liquefied gas		
Hazard Statement	Extremely flammable gas		
	Contains gas under pressure		
	May cause drowsiness and dizziness		
Prevention	Keep away from heat, sparks, open flame and hot services. No Smoking. Avoid inhaling.		
	Use in well ventilate area.		

Section 3	COMPOSITION/INFORMATION ON INGREDIENTS			
Hazardous Components	Approximate	C.A.S Number		
(chemical & common names)	Concentration %			
Petroleum Hydrocarbon		106-97-8		
Liquefied Petroleum Gas	56.5120			
N Butane	17.2794			
Iso-Butane	25.7867			
Propane	0.4219			

Section 4	FIRST AIR MEASURES
Inhalation	If adverse effects occur, remove to fresh air. If breathing is difficult oxygen should be
	administered by qualified personnel. Seek medical attention if required.
Eyes	Flush eyes with plenty of water for at least 15 minutes and seek medical advice.
Skin Contact	Wash immediately with plenty of water. If frostbite occurs seek medical attention.
Ingestion	If a large amount is swallowed do not induce vomiting. Seek medical attention.

Section 5	FIRE-FIGHTING MEASURES	
Specific Hazards	Severe explosion hazard. Vapor/air mixture are explosive. The vapor is heavier than air.	
	Vapors or gases may ignite at distant ignition sources and flash back.	
Extinguishing Media	Use dry chemical, CO2 or appropriate foam	
Fire Fighting Methods	Wear full fire-fighting gear including self-contained breathing apparatus (SCBA) for	
and Protection	protection against possible exposure.	
Hazardous	Carbon dioxide, Carbon monoxide.	
<b>Combustion Products</b>		

Section 6	ACCIDENTAL RELEASE MEASURES
Personal Precautions	Wear personal protective clothing including respiratory protection as warranted. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Environmental	Avoid release to the environment.
Precautions	
Containment Methods	Use dry chemical, CO2 or appropriate foam. Do not touch spilled material. Reduce waters
	with water spray. Contain with foam.
Cleanup Methods	Remove sources of ignition. Isolate area. Ventilate closed spaces.

Section 7	HANDLING AND STORAGE		
Handling Procedures	Keep away from heat and ignition sources. Use only with adequate ventilation. Wash		
	thoroughly after handling.		
Storage Procedures	Store in a cool/low temperature, well-ventilated place away from heat and ignition.		
Incompatibilities	Oxidizing materials.		

Section 8	EXPOSURE CONTROLS/PERSONAL PROTECTION		
Component Exposure L	imits		
Iso Butane	800 ppm (1900 mg/m3) NIOSH recommended TWA 10 hour(s)		
Liquefied Petroleum	1000 ppm (1800 mg/m3) OSHA TWA		
Gas	1000 ppm ACGIH TWA		
	1000 ppm (1800 mg/m3) NIOSH recommended TWA 10 hour(s)		
N Butane (106-97-8)	ACGIH 1000 ppm STEL		
Engineering Controls	Ventilation equipment should be explosion-resistant if explosive concentrations of material		
	are present. Ensure compliance with applicable exposure limits.		
Personal Protective Eq	uipment		
Eyes/Face	For the gas: Eye protection not required, but recommended. For the liquid: Wear splash		
	resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower		
	in the immediate work area.		
Protective Clothing	For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective,		
	cold insulating clothing.		
Gloves	Wear insulated gloves.		
Respirator	The following respirators and maximum use concentrations are drawn from NIOSH and/or		
	OSHA.		
	2000 ppm		
	Any supplied-air respirator.		
	Any self-contained breathing apparatus with a full face piece.		
	Escape - Any appropriate escape-type, self-contained breathing apparatus.		
	For Unknown Concentrations or Immediately Dangerous to Life or Health		
	Any supplied-air respirator with full face piece and operated in a pressure-demand or other		
	positive-pressure mode in combination with a separate escape supply.		
	Any self-contained breathing apparatus with a full face piece.		

Section 9	PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Liquefied gas	Appearance/Description	Colorless, gas	
Color	Colorless	Physical Form	Gas	
Odor	Unpleasant odor	Odor Threshold	6.16 ppm	
Boiling Point	-0.5 C	Flash Point	120°F	
Decomposition	N/A	Evaporation Rate	N/A	
Vapor Density (Air=1)	2.0	Specific Gravity	0.60	
Solubility in Water	Slight	Vapor Density (Air=1)	2.0	

Section 10		STABILTY AND REACTIVITY		
Reactivity	No reactivity is expected	Chemical Stability	Stable at normal temp, pressure	
Hazardous Polymerize	Will not occur	Incompatible Materials	Oxidizing materials	
Hazardous	Oxides of carbons Odor Threshold 6.16 ppm			
Decomposition				
Conditions to Avoid	Heat, flames, sparks and other sources of ignition			

Section 11 TOXICOLOGICAL INFORMATION					
Acute and Chronic To	xicity. Compone	ent Analysis –LD50/LC50	The component	s of this mater	ial have been reviewed in
various sources and t	the following sel	ected endpoints are pub	lished. Inhalatio	n LC50 rat 658	g/m3 4 h
RTECS Acute Toxicity	(selected) The o	components of this mate	rial have been re	eviewed, and R	TECS publishes the
following endpoints;					
N-Butane (106-97-8)	Inhalation:	680000 mg/m3/2 hour	Inhalation Mous	se LC50	
	658000 mg/m3/4 hour Inhalation Rat LC50				
<b>Acute Toxicity Level</b>					
Non Toxic	Inhalation	ion Immediate Effects Frostbite, central nervous system effects.			
<b>Delayed Effects</b>	No informat	No information on significant adverse effects.			
Component Carcinog	omponent Carcinogenicity  None of this products components are listed by OSHA, ACGIH, DFG, IARC or N			, ACGIH, DFG, IARC or NTP	
<b>Delayed Effects</b>	No informat	No information on significant adverse effects.			
Chronic Effects					
Mutagenic	None known.	Respiratory Sensitizer No data available.		able.	
Aspiration Hazard	Not applicable	. Reproductive Effects Data No data available		able	
Dermal Sensitizer	No data availa	ble Medical Conditions Aggravated by Exposure None known.			

Section 12		ECOLOGICAL INFORMATION		
Persistence and	No available data	No available data  Bio accumulative  Bioconcentration potential in		
Degradability	Potential aquatic organisms is moderate.			
Mobility in Soil	Low	Other Adverse Effects	No available data	

Section 13	DISPOSAL CONSIDERATIONS
Disposal Methods	Dispose in accordance will local regulations. Subject to disposal regulations: US EPA 40 CFR
	262 Hazardous Waste Number(s): D001

Section 14		TRANSPORT INFORMATION			
US DOT Information Shipping Name	Butane	UN/NA#	UN1075	Required label(s)	2.1
IMDG Information Shipping Name	Butane	UN/NA#	UN1075	Required label(s)	2.1

## Section 15 REGULATORY INFORMATION

**U.S. Federal Regulations:** None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

Section 16	OTHER INFORMATION
Last Revision Date	4/11/17
Preparation Date	4/11/17

Blazer Products makes no express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Blazer Products shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.