

Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 19-5009-6
 Version Number:
 14.01

 Issue Date:
 01/29/18
 Supercedes Date:
 02/23/16

SECTION 1: Identification

1.1. Product identifier

ScotchgardTM Cleaner For Fabric & Upholstery (CAT. NO. 1014)

Product Identification Numbers

70-0051-1089-8, 70-0712-2222-1, 70-0714-0811-9, 70-0714-2371-2, 70-0714-2556-8, 70-0714-7523-3

1.2. Recommended use and restrictions on use

Recommended use

Cleaner for fabric

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Home Care Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Gas Under Pressure: Liquefied gas.

Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Gas cylinder | Health Hazard |

Pictograms



Hazard Statements

Contains gas under pressure; may explode if heated.

Causes damage to organs: cardiovascular system

Precautionary Statements

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response:

IF exposed: Call a POISON CENTER or doctor/physician. Specific treatment (see Notes to Physician on this label).

Storage:

Protect from sunlight. Store in a well-ventilated place. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

1% of the mixture consists of ingredients of unknown acute oral toxicity. 6% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	85 - 90
Isobutane	75-28-5	3 - 7 Trade Secret *
Styrene maleic anhydride copolymer	52720-34-0	0.8 - 5
Organic Acid Ester Salt	Trade Secret*	1 - 5
1,1-Difluoroethane	75-37-6	1 - 3 Trade Secret *
SodiumLaurylSulfate	151-21-3	1 - 2 Trade Secret *
2-Butoxyethanol	111-76-2	< 0.5
Morpholine	110-91-8	< 0.2
Sodium Nitrite	7632-00-0	< 0.2
Lauryldimethylamine Oxide	1643-20-5	< 0.17

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire. Refer to other precautionary advice in SDS section 5.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Fluoride	During Combustion
Oxides of Sulfur	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Page 3 of 12

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Morpholine	110-91-8	OSHA	TWA:70 mg/m3(20 ppm)	SKIN
Morpholine	110-91-8	ACGIH	TWA:20 ppm	SKIN, A4: Not class. as
				human carcin
2-Butoxyethanol	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	SKIN
2-Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal
				carcin.
Natural gas	75-28-5	ACGIH	Limit value not established:	
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
1,1-Difluoroethane	75-37-6	AIHA	TWA:2700 mg/m3(1000 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

Page 4 of 12

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Specific Physical Form:
Aerosol

Odor, Color, Grade: Liquid mixture in aerosol container, dispenses white foam with

slight odor of ammonia.

Odor thresholdNo Data Available

pH 9.2

Melting point Not Applicable

Boiling Point 100 °C [Details:(Liquid Product)]

Flash PointNo flash pointEvaporation rateNot ApplicableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

Vapor Pressure 18 mmHg [@ 20 °C] [Details:(Liquid Product)]

Vapor Density Not Applicable

Density 1 g/ml [Details:(Liquid Product)]

Specific Gravity 1 [Ref Std: WATER=1] [Details:(Liquid Product)]

Solubility in Water Complete

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosityNo Data Available

Volatile Organic Compounds Approximately 4.8 %

Page 5 of 12

01/29/18

Percent volatile VOC Less H2O & Exempt Solvents

Approximately 94 % No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Page 6 of 12

Eve Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

No known health effects.

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isobutane	Inhalation- Gas (4 hours)	Rat	LC50 276,000 ppm
Styrene maleic anhydride copolymer	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Styrene maleic anhydride copolymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
SodiumLaurylSulfate	Inhalation- Dust/Mist		LC50 > 0.975 mg/l
SodiumLaurylSulfate	Dermal	Rabbit	LD50 580 mg/kg
SodiumLaurylSulfate	Ingestion	Rat	LD50 1,650 mg/kg
1,1-Difluoroethane	Inhalation- Gas (4 hours)	Rat	LC50 > 437,000 ppm
1,1-Difluoroethane	Ingestion	Rat	LD50 > 1,500 mg/kg
2-Butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
2-Butoxyethanol	Inhalation- Vapor (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-Butoxyethanol	Ingestion	Guinea pig	LD50 1,414 mg/kg
Morpholine	Dermal	Rabbit	LD50 310 mg/kg
Morpholine	Inhalation- Vapor	Rat	LC50 estimated to be 10 - 20 mg/l
Morpholine	Ingestion	Rat	LD50 1,050 mg/kg
Lauryldimethylamine Oxide	Ingestion	Mouse	LD50 2,700 mg/kg
Lauryldimethylamine Oxide	Dermal	Rabbit	LD50 3,536 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isobutane	Professio	No significant irritation
	nal	
	judgeme	
	nt	
SodiumLaurylSulfate	Rabbit	Irritant
2-Butoxyethanol	Rabbit	Irritant
Morpholine	official	Corrosive
	classifica	
	tion	

Serious Eye Damage/Irritation

Page 7 of 12

01/29/18

Name	Species	Value
Isobutane	Professio	No significant irritation
	nal	
	judgeme	
	nt	
SodiumLaurylSulfate	Rabbit	Corrosive
2-Butoxyethanol	Rabbit	Severe irritant
Morpholine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
2-Butoxyethanol	Guinea	Not classified
	pig	
Morpholine	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isobutane	In Vitro	Not mutagenic
1,1-Difluoroethane	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1-Difluoroethane	In vivo	Some positive data exist, but the data are not sufficient for classification
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Morpholine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Morpholine	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

curemogenery			
Name	Route	Species	Value
1,1-Difluoroethane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Morpholine	Ingestion	Multiple animal species	Not carcinogenic
Morpholine	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
1,1-Difluoroethane	Inhalation	Not classified for development	Rat	NOAEL 50,000 ppm	during organogenesi s
2-Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesi s
2-Butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesi s

Page 8 of 12

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
SodiumLaurylSulfate	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
1,1-Difluoroethane	Inhalation	cardiac sensitization	Causes damage to organs	Human and animal	NOAEL Not available	poisoning and/or abuse
1,1-Difluoroethane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL 100,000 ppm	
1,1-Difluoroethane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Morpholine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Specific Target Organ Toxicity - repeated exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
1,1-Difluoroethane	Inhalation	hematopoietic system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 25,000 ppm	2 years
2-Butoxyethanol	Dermal	blood	Not classified	Multiple	NOAEL Not	not available

Page 9 **of** 12

				animal species	available	
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
Morpholine	Dermal	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
Morpholine	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
Morpholine	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Morpholine	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.09 mg/l	13 weeks
Morpholine	Inhalation	liver kidney and/or bladder	Not classified	Rat	LOAEL 64 mg/l	5 days
Morpholine	Inhalation	heart endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
Morpholine	Inhalation	nervous system	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
Morpholine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	liver respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 800 mg/kg/day	30 days
Morpholine	Ingestion	endocrine system	Not classified	Rat	NOAEL 323 mg/kg/day	4 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Facility must be capable of handling aerosol cans. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Dhyataal	Hazards
Physical	Hazaros

Gas under pressure

Health Hazards

Specific target organ toxicity (single or repeated exposure)

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
Sodium Nitrite (ALKALI METAL NITRITES FOR	7632-00-0	Toxic Substances Control Act (TSCA) 5	Applicable
USE IN METALWORKING FLUIDS		SNUR or Consent Order Chemicals	
CONTAINING AMINES)			
Sodium Nitrite	7632-00-0	Toxic Substances Control Act (TSCA) 5	Applicable
		SNUR or Consent Order Chemicals	

Deference

This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

CASNO

ingredient (Category ii applicable)	<u>C.A.S. 110</u>	Kelefelice	
Sodium Nitrite	7632-00-0	40CFR721.4740	

15.2. State Regulations

Contact 3M for more information.

Ingradiant (Catagory if applicable)

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification

Page 11 of 12

01/29/18

and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

Aerosol Storage Code: 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride. During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

HMIS Hazard Classification

Health: 4 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 19-5009-6
 Version Number:
 14.01

 Issue Date:
 01/29/18
 Supercedes Date:
 02/23/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 12 of 12