



MATERIAL SAFETY DATA SHEET

PRODUCT NAME


STA-SHARP ADHERING LIQUID UN 1993

SECTION I

Manufacturer's Name ULANO CORPORATION	Emergency Telephone Number CHEMTREC: (800)424-9300 or (703)527-3887
Address (Number, Street,) 110 THIRD AVE.	Telephone Number for Information (718)237-4700 Fax#: (718)802-1119
(City, State, ZIP Code) BROOKLYN, NY. 11217	Date Prepared June 20, 2007
Signature of Preparer (optional)	

SECTION II - Ingredients/Identity Information

(Specific Chemical Identity; Common Name(s))

Ingredients	C.A.S. #	OSHA PEL	ACGIH TLV	APPROX. CONC.	HAZARD TYPE
HEPTANE	CAS# 142-82-5	400PPM	400PPM (I)	40%	FLAMMABLE
ETHYL ACETATE	CAS# 141-78-6	400PPM	400PPM	30%	FLAMMABLE
BUTYL ACETATE	CAS# 123-86-4	150PPM	150PPM	5%	FLAMMABLE
ISOPROPYL ALCOHOL	CAS# 67-63-0	400PPM	400PPM	25%	FLAMMABLE

THIS PRODUCT CONTAINS SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS
ULANO PRODUCTS ARE NOT MANUFACTURED WITH, NOR DO THEY CONTAIN CLASS-I OR CLASS-II OZONE DEPLETING CHEMICALS.

SECTION III - Physical/Chemical Characteristics

Boiling Point 38°F	Specific Gravity (H ₂ O=1) 0.78
vapor Pressure (mm Hg.) 76	Melting Point N.A.
Vapor Density (AIR=1) HEAVIER THAN AIR	Evaporation Rate (H ₂ O=1) HIGHER
Solubility in Water PARTIALLY SOLUBLE	
Appearance and Odor COLORLESS LIQUID, FRUIT-LIKE ODOR	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) 40°F	Flammable Limits	LEL 1.12%	UEL 6.7%
--	------------------	---------------------	--------------------

Extinguishing Media
WATER FOG, CARBON DIOXIDE OR DRY CHEMICAL

Special Fire Fighting Procedures
SELF-CONTAINED BREATHING APPARATUS WITH PRESSURE DEMAND OR POSITIVE PRESSURE SOURCES.

Unusual Fire and Explosion Hazards
VAPOR HEAVIER THAN AIR. MAY TRAVEL ALONG GROUND TO OTHER IGNITION SOURCES.

SECTION V - Reactivity Data

Stability	Unstable	Stable X
-----------	----------	--------------------

Conditions to Avoid
IGNITION SOURCES

Incompatibility (Material to Avoid)

STRONG OXIDIZING AGENTS

Hazardous Decomposition or Byproducts

COMBUSTION CAN PRODUCE CARBON DIOXIDE AND CARBON MONOXIDE

Hazardous Polymerization

May Occur

Will Not Occur

Conditions to Avoid

NONE KNOWN

HMIS

Health [2]

Flammability [3]

Reactivity [0]

Personal Protection [C]

SECTION VI - Health Hazard Data

Route(s) of Entry	Inhalation?	Skin?	Ingestion?
	X	X	X

Health Hazards (*Acute and Chronic*)
YES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION AND DEFATTING DERMATITIS. INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL IRRITATION DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Signs and Symptoms of Exposure
SKIN, EYE OR NASAL IRRITATION, DIZZINESS OR NAUSEA

Medical Condition Generally Aggravated by Exposure
NONE KNOWN

Emergency and First Aid Procedures

SKIN: WASH THOROUGHLY WITH SOAP AND WATER. WASH CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. LIFTING AND RINSING UNDER UPPER AND LOWER LIDS. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON CALM, WARM AND GET MEDICAL ATTENTION IMMEDIATELY. ASPIRATION OF MATERIAL INTO LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. IF BREATHING, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER INDIVIDUAL OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

SECTION VII - Precautions for Safe Handling and Use

Steps to be taken in case Material is Released or Spilled

STOP AND CONTAIN SPILL. ABSORB MATERIAL WITH SUITABLE MEDIA. ELIMINATE SOURCES OF IGNITION. PLACE MEDIA INTO SEALED, SOLVENT RESISTANT CONTAINER.

Waste Disposal Method

HANDLE AS AN IGNITABLE WASTE. DISPOSE OF IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.

Precautions to be Taken in Handling and Storing

KEEP AWAY FROM SPARKS, FLAMES AND OTHER SOURCES OF IGNITION. STORE AND USE ONLY WITH PROPER VENTILATION. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID CONTACT WITH SKIN AND EYES.

Other Precautions

PREVENT BUILD UP OF VAPORS. EXTINGUISH ALL PILOT LIGHTS AND HEATERS THAT COULD CAUSE IGNITION OF FUMES.

SECTION VIII - Control Measures

Respiratory Protection (*Specify Type*)

IN THE CASE OF A LARGE SPILL, USE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS.

Ventilation

Local Exhaust	Mechanical (<i>General</i>)	Special	Other
	X		

Protective Gloves

SOLVENT RESISTANT RUBBER GLOVES

Eye Protection

NIOSH APPROVED GOGGLES

Other Protective Clothing or Equipment

IMPERVIOUS APRON

Work / Hygienic Practices

WORK CAREFULLY, AVOID SPILLS.

WHILE THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF ULANO CORP. MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.