

OMNI-PAK®

Please refer to separate material safety data information for the paint contents.

B45116

OMNI-PAK® MasterBlend™ &
OMNI-PAK® MasterBlend™ EZ TOUCH®

Material Safety Data Sheet

MANUFACTURER'S NAME:

The Sherwin-Williams Company • 101 Prospect Avenue N.W. • Cleveland, OH 44116

EMERGENCY TELEPHONE NO.: (216) 666-2817

DATE OF PREPARATION: 12-JAN-00

Section I - PRODUCT IDENTIFICATION

PRODUCT NUMBER: B45116, B45112, B45106 & B45216

HMIS CODE: Health 2 Flammability 4 Reactivity 0

PRODUCT NAME: OMNI-PAK® MasterBlend™ & OMNI-PAK® MasterBlend™ EZ TOUCH®

PRODUCT CLASS: Aerosol Specialty Product

Section II - HAZARDOUS INGREDIENTS

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	M.P.
Propane 74-98-6	26	2500	1000	PPM	760.00
Acetone 67-64-1	66 STEL	500 760	1000	PPM PPM	180.00
Methyl Ethyl Ketone 78-93-3	9 STEL	200 300	200 300	PPM PPM	70.00
Ethyl 3-Ethoxypropionate 783-69-6	1	Not Established			1.11

Section III - PHYSICAL DATA

PRODUCT WEIGHT: 1.86 lb./gal.

SPECIFIC GRAVITY: 0.70

BOILING POINT: < 0 °F

VOLATILE VOLUME: 100 %

VOLATILE WEIGHT: 5.47 % (less Federally Exempt Solvents)

HMIS: 2 4 0

EVAPORATION RATE: Faster than Ether

VAPOR DENSITY: Heavier than Air

MELTING POINT: N.A.

SOLUBILITY IN WATER: N.A.

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Propellant < 0 °F

LEL UEL
1.0 12.0

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V - HEALTH HAZARD DATA

ROUTES OF EXPOSURE: Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE HEALTH HAZARDS:

EFFECTS OF OVEREXPOSURE: Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

EMERGENCY AND FIRST AID PROCEDURES:

IF INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
IF ON SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
IF IN EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
IF SWALLOWED: Get medical attention.

CHRONIC HEALTH HAZARDS: No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Methyl Ethyl ketone may increase the nervous system effects of other solvents. Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to reproductive systems. Reports have associated reported and prolonged overexposure to solvents with permanent brain and nervous system damage.

STABILITY: Stable

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate and remove with inert absorbent. **WASTE DISPOSAL METHOD:** Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII - PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION: Local exhaust preferable, general exhaust acceptable if the exposure to material in Section II is maintained below applicable exposure limits. Refer to OSHA Standard: 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION: Wear safety spectacles with unperforated sideshields.

DOL STORAGE CATEGORY: 1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone; Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code: Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS: Intentional misuse, by deliberately concentrating and inhaling the contents can be harmful or fatal.

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION:

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
78-93-3	Methyl Ethyl Ketone	9	

CALIFORNIA PROPOSITION 85:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
TSCA CERTIFICATION: All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.