Safety Data Sheet



Section 1: Identification

Product identifier

Product Name • HEET® Gas Line Antifreeze Line

Synonyms • 584402

Product Code • 28201; 28203; 28205; 28213; 28219

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Gasoline fuel additive

Restrictions on use

• Do not use in diesel fuel or add to gasoline/oil mixtures use in 2 cycle engines

Details of the supplier of the safety data sheet

Manufacturer
 Gold Eagle Co.

4400 S. Kildare Avenue Chicago, IL 60632-4372

United States

http://www.goldeagle.com/

Telephone (General) • 773-376-4400

Emergency telephone number

• 1-800-535-5053 - (INFOTRAC #22283)

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Flammable Liquids 2

Skin Irritation 2
Eye Irritation 2

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Reproductive Toxicity 2

Specific Target Organ Toxicity Single Exposure 1
Specific Target Organ Toxicity Repeated Exposure 1

Label elements
OSHA HCS 2012

DANGER







Hazard statements · Highly flammable liquid and vapour

Causes skin irritation
Causes serious eye irritation

Preparation Date: 23/September/2014 Revision Date: 11/September/2015

Page 1 of 11

May cause drowsiness or dizziness

Suspected of damaging fertility or the unborn child.

Causes damage to organs - Eyes

Causes damage to organs - Eyes through prolonged or repeated exposure

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Keep container tightly closed.

Ground and/or bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist/vapours/spray. Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection , .

Response • In case of fire: Use appropriate media for extinction.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse.

If skin irritation occurs: Get medical advice/attention. Specific treatment, see supplemental first aid information.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell.

IF exposed: Call POISON CENTER or doctor/physician.

Storage/Disposal • Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

OSHA HCS 2012

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance.

Mixtures

			Composition	
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive
			Inhalation-Rat LC50 •	

Methanol	CAS: 67-56-1	100%	64000 ppm 4 Hour(s) Skin-Rabbit LD50 • 15800 mg/kg Ingestion/Oral-Rat LD50 • 5600 mg/kg	OSHA HCS 2012: Flam. Liq. 2; Eye Irrit. 2; Skin Irrit. 2; STOT SE 1 (Eyes); STOT SE 3: Narc.; STOT RE 1 (Eyes); Repr. 2
Proprietary	Proprietary	0.0006% TO 0.0012%	Ingestion/Oral-Rat LD50 • 4300 mg/kg Inhalation-Rat LC50 • 5000 ppm 4 Hour(s) Skin-Rabbit LD50 • >1700 mg/kg	OSHA HCS 2012: Exposure limit(s)
Proprietary	Proprietary	0.0001996% TO 0.0003996%	Skin-Rabbit LD50 • 17800 µL/kg Ingestion/Oral-Rat LD50 • 3500 mg/kg Inhalation-Rat LC50 • 55000 mg/m³ 2 Hour(s)	OSHA HCS 2012: Exposure limit(s)

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.

Skin

 In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. Wash skin with soap and water.

Eye

 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Get medical attention immediately.

Ingestion

 Induce vomiting (only in conscious persons) Then give 2 teaspoons of baking soda in a glass of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Use halon replacement or carbon dioxide extinguishers or alcohol foam for small fires. Large fires should be extinguished with alcohol foam.

Unsuitable Extinguishing Media

Water spray or fog can cool fire but may not be effective in extinguishing fire.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

Containers may explode when heated.

Vapor explosion hazard indoors, outdoors or in sewers.

HIGHLY ELAMMARIE: Will be easily ignited by heat an

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Many liquids are lighter than water.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Runoff to sewer may create fire or explosion hazard.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

· No data available

Advice for firefighters

Structural firefighters' protective clothing will only provide limited protection.
Wear positive pressure self-contained breathing apparatus (SCBA).
Move containers from fire area if you can do it without risk.
LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Ventilate the area. Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist, vapours and/or spray. Avoid contact with skin, eyes, and clothing.

Emergency Procedures

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

• Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

• Stop leak if you can do it without risk.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Use only with adequate ventilation. Keep away from heat, sparks, and flame. All
equipment used when handling the product must be grounded. Take precautionary
measures against static charges. Do not use sparking tools. Contact lenses should
not be worn when working with this chemical. Wear appropriate personal protective
equipment, avoid direct contact. Do not breathe mist, vapours and/or spray. Avoid
contact with skin, eyes, and clothing. Wash thoroughly with soap and water after
handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage

Keep container tightly closed. Keep away from sources of ignition – No Smoking.
 Store in a cool, dry, well-ventilated place. Empty containers contain product residues, assume emptied containers to have same hazards as full containers.

Section 8 - Exposure Controls/Personal Protection

Control parameters

		Exposure	Limits/Guidelines	
	Result	ACGIH	NIOSH	OSHA
Proprietary	TWAs	20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA
(Proprietary)	STELs	Not established	125 ppm STEL; 545 mg/m3 STEL	Not established
Proprietary	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA
(Proprietary)	STELs	150 ppm STEL	Not established	Not established
Methanol	TWAs	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA	200 ppm TWA; 260 mg/m3 TWA
(67-56-1)	STELs	250 ppm STEL	250 ppm STEL; 325 mg/m3 STEL	Not established

Exposure controls

Engineering Measures/Controls Good general ventilation should be used. Ventilation rates should be matched to
conditions. If applicable, use process enclosures, local exhaust ventilation, or other
engineering controls to maintain airborne levels below recommended exposure limits.
If exposure limits have not been established, maintain airborne levels to an acceptable
level. Use only appropriately classified electrical equipment.

Personal Protective Equipment

Respiratory

 In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

· Wear chemical splash safety goggles.

Skin/Body

Wear appropriate gloves. Wear protective clothing

Environmental Exposure Controls

Controls should be engineered to prevent release to the environment, including
procedures to prevent spills, atmospheric release and release to waterways. Follow
best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene NIOSH = National Institute of Occupational Safety and Health OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Water-white to pale yellow liquid.
Color	Water-white to pale yellow.	Odor	No data available
Odor Threshold	No data available		
General Properties		•	-
Boiling Point	147 F(63.8889 C)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	= 0.791 Water=1	Water Solubility	Soluble 100 %
Viscosity	3 to 5 Centistoke (cSt, cS) or mm2/sec @ 40 C(104 F)		
Volatility		•	
Vapor Pressure	96 mmHg (torr)	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Vol.)	100 %
Volatiles (Vol.)	100 %		
Flammability	-	-	•

Flash Point	56 F(13.3333 C)	UEL	12.7 %
LEL	2 %	Autoignition	No data available
Flammability (solid, gas)	Not relevant.		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

· No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization will not occur.

Conditions to avoid

· Keep away from heat, sparks, and flame.

Incompatible materials

• Strong oxidizing agents, aluminum, zinc, or metals that displace hydrogen, rubber and rubber based coatings, chromic anhydride, lead perchlorate and perchloric acids.

Hazardous decomposition products

Excessive heating and/or incomplete combustion will produce carbon monoxide.

Section 11 - Toxicological Information

Information on toxicological effects

	Components
■Methanol ■	 Acute Toxicity: Ingestion/Oral-Rat LD50 • 5600 mg/kg; Inhalation-Rat LC50 • 64000 ppm 4 Hour(s); Skin-Rabbit LD50 • 15800 mg/kg; Irritation: Eye-Rabbit • 100 mg 24 Hour(s) • Moderate irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Mutagen: Cytogenetic analysis • Ingestion/Oral-Mouse • 1 g/kg; DNA damage • Ingestion/Oral-Rat • 10 µmol/kg; Reproductive: Inhalation-Mouse TCLo • 5000 ppm 7 Hour(s)(6-15D preg); Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue); Inhalation-Mouse TCLo • 2000 ppm 7 Hour(s)(6-15D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012 • Data lacking
Serious eye damage/Irritation	OSHA HCS 2012 • Eye Irritation 2
Acute toxicity	OSHA HCS 2012 • Data lacking
Aspiration Hazard	OSHA HCS 2012 • Data lacking
Carcinogenicity	OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	OSHA HCS 2012 • Data lacking
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1

STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 1; Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Toxicity for Reproduction	OSHA HCS 2012 • Toxic to Reproduction 2
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking

Potential Health Effects

Inhalation

Acute (Immediate)

• May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

No data available.

Skin

Acute (Immediate)

· Causes skin irritation.

Chronic (Delayed)

· No data available.

Eye

Acute (Immediate)

· Causes serious eye irritation.

Chronic (Delayed)

· No data available.

Ingestion

Acute (Immediate)

 May cause headache, dizziness, weakness, euphoria, drowsiness, shortness of breath, vomiting, and loss of voluntary muscle control. Can also cause blindness and death.

Chronic (Delayed)

No data available.

Other

Chronic (Delayed)

 Chronic poisoning from repeated exposure to methanol vapor were manifested by conjunctivitis, headache, giddiness, insomnia, gastric disturbances, and bilateral blindness.

Carcinogenic Effects

 This product does not contain any components above de minimus concentrations that are considered carcinogenic by OSHA, IARC or NTP.

		Carcinogenic Effects
	CAS	IARC
Proprietary	Proprietary	Group 2B-Possible Carcinogen

Reproductive Effects

Animal tests for components have shown adverse reproductive effects.

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

 Non-mandatory section - information about this substance not complied for this reason.

Persistence and degradability

 Non-mandatory section - information about this substance not complied for this reason.

Bioaccumulative potential

 Non-mandatory section - information about this substance not complied for this reason.

Mobility in Soil

Format: GHS Language: English (US)
OSHA HCS 2012

Non-mandatory section - information about this substance not complied for this

Other adverse effects

Non-mandatory section - information about this substance not complied for this

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	ORM-D	Consumer commodity	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Acute, Chronic, Fire

		Inventory
Component	CAS	TSCA
Proprietary	Proprietary	Yes
Methanol	67-56-1	Yes
Proprietary	Proprietary	Yes

United States

S OSHA - Process Safety Management - High	ly Hazardous Chemicals	
Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
Proprietary	Proprietary	Not Listed
S OSHA - Specifically Regulated Chemicals		
Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
Proprietary	Proprietary	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Proprietary	Proprietary	(listed under Ethyl benzene)
Methanol	67-56-1	
Proprietary	Proprietary	(isomers and mixtures)
U.S CAA (Clean Air Act) - Accidental Release Prevention - Flammable Subst	tances	
• Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
• Proprietary	Proprietary	Not Listed
U.S CAA (Clean Air Act) - Accidental Release Prevention - Toxic Substances	s	
Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
• Proprietary	Proprietary	Not Listed
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities	6	
• Proprietary	Proprietary	1000 lb final RQ; 454 kg final RQ
Methanol	67-56-1	5000 lb final RQ; 2270 kg final RQ
• Proprietary	Proprietary	100 lb final RQ; 45.4 kg final RQ
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA R	(Qs	
Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
• Proprietary	Proprietary	Not Listed
	,	
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
• Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
Proprietary	Proprietary	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
Proprietary	Proprietary	0.1 % de minimis concentration
		1.0 % de minimis
Methanol	67-56-1	concentration
Dramiatory	Dua nuiata nu	1.0 % de minimis
Proprietary	Proprietary	concentration
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Proprietary	Proprietary	Not Listed
Methanol	67-56-1	Not Listed
• Proprietary	Proprietary	Not Listed
U.S CWA (Clean Water Act) - Hazardous Substances		
• Proprietary	Proprietary	
Methanol	67-56-1	Not Listed
• Proprietary	Proprietary	
U.S CWA (Clean Water Act) - Toxic Pollutants		
U.S CWA (Clean Water Act) - Toxic Pollutants • Proprietary	Proprietary	
	Proprietary 67-56-1	Not Listed

United States - California

Environment					
 U.S California - Proposition 65 - Carcinogens List • Proprietary • Methanol • Proprietary 	Proprietary 67-56-1 Proprietary	carcinogen, initial date 6/11/04 Not Listed Not Listed			
			U.S California - Proposition 65 - Developmental Toxicity • Proprietary	Proprietary	Not Listed
			Methanol	67-56-1	developmental toxicity, initial date 3/16/12
			 Proprietary U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL) 	Proprietary	Not Listed
• Proprietary	Proprietary	Not Listed			
Methanol	67-56-1	Not Listed			
• Proprietary	Proprietary	Not Listed			
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)					
• Proprietary	Proprietary	54 μg/day NSRL (inhalation); 41 μg/day NSRL (oral)			
Methanol	67-56-1	Not Listed			
• Proprietary	Proprietary	Not Listed			
U.S California - Proposition 65 - Reproductive Toxicity - Female					
• Proprietary	Proprietary	Not Listed			
Methanol	67-56-1	Not Listed			
• Proprietary	Proprietary	Not Listed			
U.S California - Proposition 65 - Reproductive Toxicity - Male					
• Proprietary	Proprietary	Not Listed			
Methanol	67-56-1	Not Listed			
Proprietary	Proprietary	Not Listed			

Other Information

• WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Section 16 - Other Information

Revision Date

Preparation Date

Other Information

Disclaimer/Statement of Liability

- 11/September/2015
- 23/September/2014
- Schedule B Number: 3820.00.0000.
- Information presented herein is believed to be factual, as it has been derived from the
 works and opinions of persons believed to be qualified experts. However, nothing
 contained in this information is to be taken as warranty or representation for which the
 Gold Eagle Co. bears legal responsibility. The user should review any
 recommendations in the specific context of the intended use to determine whether

they are appropriate.

Key to abbreviations NDA = No data available