

Product Number: 6029

## Section 1: Manufacturer Identification

Mason Color Works, Inc.  
250 East 2<sup>nd</sup> Street/P.O. Box 76  
East Liverpool, OH 43920-5076

Phone: (330) 385-4400  
Fax: (330) 385-4488

## Section 2: Identification of Product

Chemical Family: Inorganic  
Product Names: Persimmon 6029  
Chemical Abstract Number (CAS): 68186-88-9, 68201-65-0, 65997-18-4  
Chemical Name: Chrome Alumina Zinc Pink - Spinel  
Chemical Formula:  $\text{Zn(Al,Cr)}_2\text{O}_4$

## Section 3 &amp; Section 4: Hazardous ingredients Identity/Information and Overexposure Symptoms

|                                                              | ACGIH-TLVs                   | OSHA PELs                                                        | NOISHA RELs |
|--------------------------------------------------------------|------------------------------|------------------------------------------------------------------|-------------|
| Alumina Oxide ( $\text{Al}_2\text{O}_3$ )<br>Cas # 1344-28-1 | 10 mg/m <sup>3</sup> (total) | 15 mg/m <sup>3</sup> (total)<br>5 mg/m <sup>3</sup> (respirable) | N/A         |

ACGIH: The value for particulate matter containing no asbestos and 1% crystalline silica.

Symptoms of overexposure:

**Inhalation:** Acute may cause coughing and shortness of breath. Chronic may adversely effect breathing capacity.

**Eye Contact:** Direct contact may cause irritation.

**Skin Contact:** May cause abrasions.

**Ingestion:** May cause irritation.

|                                                             |                       |                       |                       |
|-------------------------------------------------------------|-----------------------|-----------------------|-----------------------|
| Chrome Oxide ( $\text{Cr}_2\text{O}_3$ )<br>Cas # 1313-13-2 | 0.5 mg/m <sup>3</sup> | 0.5 mg/m <sup>3</sup> | 0.5 mg/m <sup>3</sup> |
|-------------------------------------------------------------|-----------------------|-----------------------|-----------------------|

ACGIH: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of carcinogenicity in humans/animals.

Symptoms of overexposure:

**Inhalation:** Repeated prolonged exposure to trivalent compounds may cause delayed effects involving the respiratory system.

**Eye Contact:** mechanical irritation to the eye may occur such as watering, reddening de to exposure to fines.

**Skin Contact:** Expected to be non irritating.

**Ingestion:** Considered to be non-irritating , non-toxic if swallowed.

|                                                           |                     |                      |                     |
|-----------------------------------------------------------|---------------------|----------------------|---------------------|
| Iron Oxide ( $\text{Fe}_2\text{O}_3$ )<br>Cas # 1309-37-1 | 5 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> | 5 mg/m <sup>3</sup> |
|-----------------------------------------------------------|---------------------|----------------------|---------------------|

ACGIH: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans/animals. The value is for particulate matter containing no asbestos and 1% crystalline silica.

**Iron Oxide cont'd**

Symptoms of overexposure:

**Inhalation:** Repeated and prolonged exposure may cause beginnings Pneumoconiosis called Siderosis.

**Eye Contact:** May cause irritation.

**Skin Contact:** May cause mechanical skin irritation.

**Ingestion:** Expected to be non-toxic.

|                                        |                       |                      |                        |
|----------------------------------------|-----------------------|----------------------|------------------------|
| Silica, Crystalline ( $\text{SiO}_2$ ) | 0.1 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> | 0.05 mg/m <sup>3</sup> |
|----------------------------------------|-----------------------|----------------------|------------------------|

Symptoms of overexposure:

**Inhalation:**

- Prolonged exposure to respirable crystalline silica (quartz) can cause Silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Silicosis increases risk of Tuberculosis.
- Inhaled from occupational sources is classified as carcinogenic to humans. (cancer)
- There is evidence that exposure to respirable crystalline silica or that the disease Silicosis is associated with increased incidence of Scleroderma, an auto-immune disorder manifested by fibrosis (scarring) of the skin and internal organs.
- There are several studies suggesting that exposure to respirable silica or that the disease Silicosis is associated with the increased incidence of kidney disorders. (Nephrotoxicity)

**Eye Contact:** May cause abrasions of the cornea.

**Skin Contact:** Not applicable.

**Ingestion:** Not applicable.

**Zinc Oxide (ZnO)**

10 mg/m<sup>3</sup>

10 mg/m<sup>3</sup> (Total)

5 mg/m<sup>3</sup>

Cas # 1314-13-2

5 mg/m<sup>3</sup> (Respirable)

Symptoms of overexposure:

**Inhalation:** High levels of dust may result in tightness of chest, metallic taste, cough, dizziness, fever, chills, headache, nausea, and dry throat. Chronic exposure may produce symptoms known as metal fume fever or "zinc shakes", an acute, self-limiting condition without recognized complications. Symptoms of metal fume fever include: chills, fever, muscular pain, nausea and vomiting. May aggravate respiratory conditions.

**Eye Contact:** May cause irritation.

**Skin Contact:** May cause irritation.

**Ingestion:** May cause irritation to the gastro-intestinal tract.

Section 5: Emergency and First Aid Procedures:

Eye: flush thoroughly with water for 15 minutes.

Skin: remove contaminated clothing, wash thoroughly with soap and water.

Inhalation: remove to fresh air, may give oxygen if needed.

Ingestion: give large amounts of water to induce vomiting, only in conscious persons.

IF THESE FIRST AID MEASURES FAIL, CONSULT PHYSICIAN!!!!!!!!!!!!!!!!!!!!!!

Principal Routes of Entry:

**Inhalation:** Dust from this product may cause irritation of the respiratory system.  
Overexposure may cause lung damage.

**Ingestion:** Large amounts may cause irritation of the gastrointestinal tract, nausea, vomiting and diarrhea.

**Skin & Eye:** Nuisance dust, prolonged or repeated may cause irritation.

Section 6: Special Protection Information

**Respiratory Protection:** Use only NIOSHA/OSHA approved respiratory protection with adequate ventilation; avoid breathing dust. Do not exceed Occupational Exposure Limits. Wash thoroughly after handling. No food or beverage should be consumed in work area.

**Personal Protective Equip:** Wear appropriate gloves and goggles to avoid skin and eye contact. Safety showers and eye stations must be present in work stations.

**Ventilation:** Use local exhaust or mechanical such as a dust collector to maintain dust levels below Occupational Exposure Limits.

Section 7: Physical and Chemical Characteristics

Boiling Point: N/A

Solubility in water: trace

Vapor Pressure (mmHg): N/A

Vapor Density (air=1): N/A

Appearance: pinkish powder

Odor: odorless

Specific Gravity (water=1): N/A

Evaporation rate: None

% Volatile by volume: None

## Section 8: Reactivity Data

Stability: Stable

Hazardous Polymerization: will not occur

Incompatibility: None

Hazard Decomposition of product: N/A

## Section 9: Fire and Explosive Data

Flash point: N/A

Flammable Limits: None

Unusual Fire and Explosion Hazard: None expected

Extinguishing Media: Carbon dioxide, dry chemical or water

Special Fire Fighting Procedures: Wear self contained breathing apparatus when large quantities involved.

## Section 10: Spill or Leak Procedures:

Contain spillage and scoop or vacuum. Avoid making dust, put in appropriate container for disposal.

Waste disposal method in accordance with Federal, State and Local Laws.

*This product is a blend of various metal oxides, salts and some compounds which are interfused by high calcination to form the finished product. Section III, Hazardous Ingredients Identity/Information, and Section IV, Symptoms of Overexposure, pertain to individual components. Section V through Section X are in reference to the finished product.*

**\*\*\*\*\*Attention All Retailers of Mason Stains\*\*\*\*\***

***ALL retailers of this product are REQUIRED by law to supply their customers with a copy of this material safety data sheet with initial purchase.***

### **\*\*\*SARA 313**

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (SARA) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CFR, Part 372.

**The information contained in this Material Safety Data Sheet must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.**

**PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY ! MATERIAL SAFETY DATA SHEETS ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.**

## **DISCLAIMER**

***Mason Color Works, Inc. believes the information contained in this material safety data sheet is believed to be accurate and reliable as of the date of publication or revision but makes no warranty that it is. This information provided should be made available as required by the Federal OSHA Hazard Communication Standard 1910.1200 to ANYONE who handles, uses, stores, transports or will otherwise be exposed to this product. Mason Color Works, Inc. Accepts no Responsibility for the health or safety of any individual who misuses this product by not complying with manufacturer's instructions contained herein or additional / other measures that may be required under particular conditions.***

Last issued: 11/97  
Updated : 3/2000