

MSDS Number: **N2970** * * * * * *Effective Date: 09/15/09* * * * * *

Supersedes: 07/20/07



Material Safety Data Sheet

From: Mallinckrodt Baker, Inc.
222 Red School Lane
Phillipsburg, NJ 08865



24 Hour Emergency Telephone: 908-859-2151
CHEMTREC: 1-800-424-9300

National Response in Canada
CANUTEC: 613-996-6666

Outside U.S. And Canada
Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.

Nickelous Carbonate

1. Product Identification

Synonyms: Nickel (II) Carbonate; Carbonic Acid, Nickel Salt; C.I. 77779

CAS No.: 3333-67-3

Molecular Weight: 118.70

Chemical Formula: NiCO₃

Product Codes: 2764

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent
Hazardous		
-----	-----	-----

Nickel Carbonate	3333-67-3	99 - 100%
Yes		

3. Hazards Identification

Emergency Overview

WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY CAUSE NASAL OR LUNG DAMAGE. MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION. CANCAER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Cancer Causing)

Flammability Rating: 0 - None

Reactivity Rating: 1 - Slight

Contact Rating: 3 - Severe (Life)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: Green (General Storage)

Potential Health Effects

Inhalation:

Can cause headaches, dizziness, and difficult breathing. Finer dust particulates may irritate the respiratory tract. Symptoms may include coughing, sore throat, and shortness of breath. Inhalation of nickel and nickel compounds is associated with nasal and lung damage and cancer.

Ingestion:

May cause irritation to the gastro-intestinal tract. Large oral dose may cause nausea, vomiting, abdominal pain and diarrhea.

Skin Contact:

Causes irritation, redness, pain. May cause allergic dermatitis. Nickel is a contact allergen and sensitizer.

Eye Contact:

Causes irritation, redness, and pain.

Chronic Exposure:

Prolonged exposure to excessive concentrations of dust may cause chronic pulmonary

disorders. Nickel and certain nickel compounds are considered carcinogenic and noted for producing nasal and lung cancer.

Aggravation of Pre-existing Conditions:

Skin contact with some nickel compounds in sensitive individuals may cause dermatitis (nickel itch).

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact:

Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard.

Explosion:

Not considered to be an explosion hazard.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Toxic gases and vapors such as nickel carbonyl may be released in a fire involving nickel.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower, dispose of outer clothing, change to clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

For Nickel, Metal and Insoluble Compounds, as Ni:

- OSHA Permissible Exposure Limits (PEL) -
1 mg/m³ (TWA).

For Nickel, Elemental / Metal:

- ACGIH Threshold Limit Value (TLV) -
1.5 mg/m³ (TWA), A5 - Not suspected as a human carcinogen.

For Nickel, Insoluble Compounds, as Ni:

- ACGIH Threshold Limit Value (TLV) -
0.2 mg/m³ (TWA), A1 - Confirmed human carcinogen

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half

facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Light green powder.

Odor:

Odorless.

Solubility:

Negligible.

Specific Gravity:

No information found.

pH:

No information found.

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

No information found.

Melting Point:

Decomposes before reaching melting point.

Vapor Density (Air=1):

Not applicable.

Vapor Pressure (mm Hg):

Not applicable.

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition. Toxic gases and vapors such as nickel carbonyl may be released.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

For Nickel: Aluminum, aluminum trichloride, ethylene, p-dioxan, hydrogen, methanol, non-metals, oxidants, sulfur compounds. Slowly attacked by dilute hydrochloric or sulfuric acid; readily attacked by nitric acid. Not attacked by fused alkali hydroxides.

Conditions to Avoid:

Incompatibles.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure. Investigated as a tumorigen and mutagen.

-----\Cancer Lists\-----			
Ingredient Category	---NTP Carcinogen---		IARC
	Known	Anticipated	

Nickel Carbonate (3333-67-3)	No	Yes	1

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Regulatory Information

```
-----\Chemical Inventory Status - Part 1\-----
--
Ingredient                                TSCA   EC     Japan
Australia
-----
Nickel Carbonate (3333-67-3)              Yes    Yes    Yes     Yes

-----\Chemical Inventory Status - Part 2\-----
--
Ingredient                                Korea  DSL    NDSL    Phil.
-----
Nickel Carbonate (3333-67-3)              Yes    Yes    No      Yes

-----\Federal, State & International Regulations - Part 1\-----
--
--SARA 302-      -----SARA 313-----
--
Ingredient      RQ    TPQ    List  Chemical
Catg.
-----
Nickel Carbonate (3333-67-3)      No    No     No    Nickel compo

-----\Federal, State & International Regulations - Part 2\-----
--
--RCRA-      -TSCA-
```

Ingredient	CERCLA	261.33	8(d)
Nickel Carbonate (3333-67-3)	No	No	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No
Reactivity: No (Pure / Solid)

WARNING:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Australian Hazchem Code: None allocated.

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: **2** Flammability: **0** Reactivity: **0**

Label Hazard Warning:

WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY CAUSE NASAL OR LUNG DAMAGE. MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION. CANCER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.

Label Precautions:

Wash thoroughly after handling.
Do not breathe dust.
Keep container closed.
Use only with adequate ventilation.
Do not get in eyes, on skin, or on clothing.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of skin contact, immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. In all cases, get medical attention.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety

Phone Number: (314) 654-1600 (U.S.A.)